Patent Number: [11]

5,066,105

Date of Patent: [45]

Nov. 19, 1991

[54]	LIQUID CRYSTAL DISPLAY DEVICE
	HAVING VARISTOR LAYERS
	SUBSTANTIALLY FREE FROM
	CROSS-TALK

[75]	Inventors:	Hataaki Yoshimoto, Chiba; Katsuhiro	
		Ito, Ichihara, both of Japan	

[73] Assignee: UBE Industries, Ltd., Ube, Japan

[21] Appl. No.: 599,114

[22] Filed: Oct. 17, 1990

[30] Foreign Application Priority Data

Oct	t. 18, 1989 [JP]	Japan	1-268999
[51]	Int. Cl.5	•••••	G02F 1/13
[52]	U.S. Cl	•••••	359/58; 340/784;
			359/55
[58]	Field of Searc	h	350/333, 334, 336;
			340/784, 719

[56] References Cited

U.S. PATENT DOCUMENTS

4,427,266	1/1984	Hosokawa	350/333
4,642,620	2/1987	Togashi et al	340/719 X
4,660,030	4/1987	Maszawa	340/784
4,842,372	6/1989	Toyama	350/334
4,871,234	10/1989	Suzuki	350/333
4,990,905	2/1991	Kuijk	340/784 X

FOREIGN PATENT DOCUMENTS

2050031 12/1980 United Kingdom 350/333

OTHER PUBLICATIONS

Castleberry, "Varistor Controlled Multiplexed Liquid Crystal Display", Conference Record of the 1978 Biennial Display, Research Conference Cherry Hill, N.Y., Oct. 1978.

"Two-Terminal Active Matrix LCD Using Al2O3", IBM Technical Disclosure Bulletin, vol. 28, No. 12, May 1986.

Baraff et al., "A 68 Line Multiplexed Liquid Crystal Display Using MIM Devices", Conference: International Electron Devices Meeting, Washington, D.C., Dec. 1980.

Primary Examiner-Stanley D. Miller Assistant Examiner-Huy K. Mai Attorney, Agent, or Firm-Finnegan, Henderson, Farabow, Garrett & Dunner

[57] **ABSTRACT**

A liquid crystal display device, capable of displaying clear images without cross-talk, comprises (a) a first transparent base, (b) a plurality of picture element electrodes on the first base, (c) a plurality of signal lines on the first base, (d) a second transparent base in parallel to the first base, (e) a plurality of scanning electrodes on the second base, (f) a plurality of transit electrodes on the second base and (g) a liquid crystal material layer arranged between the picture element electrodes and the scanning electrodes. The transit electrode is connected to the corresponding picture element electrode and signal lines through two separate connecting layers, at least one of which layers comprises fine varistor particles, or through a single connecting layer comprising fine varistor particles.

8 Claims, 5 Drawing Sheets

